



		Class	Weight
1	Cover according to standart EN124 (☒)	A35 (3,5 t) □	13 kg
		B125 (12,5 t) □	45 kg
		C250 (25 t) □	55 kg
		D400 (40 t) □	90 kg
2	Maintenance shaft (☒)	800...1000 □	31 kg
		1000...1250 □	33 kg
		1250...1500 □	42 kg
		1500...1750 □	52 kg
		1750...2000 □	62 kg
		2000...2250 □	71 kg
		2250...2500 □	80 kg
3	Ladder		
4	Storage capacity for grease	640 l	
5	Grease separation chamber	2730 l	
6	Sludge trap	1030 l	
7	Grease level alarm sensor (☒)	□	
		Nominal flow rate	10 l/s
		Total capacity	4400 l
		Weight excluding manhole shaft/lid	300 kg

Product	GR	Name	Grease separator Greasly 10		Scale	1:50		
Design by	M.Skuzinskas	Checked by	E.Mozuraitis	Approved by	E.Kuodis	Drawing type		
				Construction site	Customer drawing			
				Drawing no.		Date	Lang.	Sheet
						12/2/2015	en	1



UAB ENEKA
 Vandziogalos g. 94 LT-47467 Kaunas,
 Lithuania
 tel. +37037377441, faks. +37037377907
 www.eneka.lt, info@eneka.lt