



		Class	Weight
1	Cover according to standart EN124 (☒)	A35 (3,5 t) □	13 kg
		B125 (12,5 t) □	45 kg
		C250 (25 t) □	55 kg
		D400 (40 t) □	90 kg
2	Maintenance shaft (☒)	800...1000 □	31 kg
		1000...1250 □	33 kg
		1250...1500 □	42 kg
		1500...1750 □	52 kg
		1750...2000 □	62 kg
		2000...2250 □	71 kg
		2250...2500 □	80 kg
3	Ladder		
4	Storage capacity for grease	200 l	
5	Grease separation chamber	970 l	
6	Sludge trap	230 l	
7	Grease level alarm sensor (☒)	□	
		Nominal flow rate	2 l/s
		Total capacity	1400 l
		Weight excluding manhole shaft/lid	140 kg

Product	GR	Name	Grease separator Greasly 2		Scale	1:50	
Design by	M.Skuzinskas	Checked by	E.Mozuraitis	Approved by	E.Kuodis	Drawing type	
				Construction site	Customer drawing		
					Drawing no.		
					Date	Lang.	Sheet
					12/1/2015	en	1

**UAB EHEKA**  
 Vandziogalos g. 94 LT-47467 Kaunas,  
 Lithuania  
 tel. +37037377441, faks. +37037377907  
 www.eneka.lt, info@eneka.lt