



1	Cover according to standard EN124 (☒)	Class	Weight
		A35 (3,5 t) □	13 kg
2	Maintenance shaft (☒)	B125 (12,5 t) □	45 kg
		C250 (25 t) □	55 kg
		D400 (40 t) □	90 kg
		800...1000 □	31 kg
		1000...1250 □	33 kg
		1250...1500 □	42 kg
		1500...1750 □	52 kg
3	Ladder	1750...2000 □	62 kg
		2000...2250 □	71 kg
4	Automatic closure	2250...2500 □	80 kg
5	Coalescing modules		
6	Oil storage capacity	260 l	
7	Effective capacity	1400 l	
8	Oil level alarm sensor (☒)	□	
		Nominal flow rate	6 l/s
		Total capacity	1600 l
		Weight excluding manhole shaft/lid	200 kg

Product	NS	Name	Oil/water separator SEPKO 6	Scale	1:50
Design by	M.Skužinskas	Checked by	E.Mozūraitis	Approved by	E.Kuodis
 UAB ENEKA Vandziogalos g. 94 LT-47467 Kaunas, Lithuania tel. +37037377441, faks. +37037377907 www.eneka.lt, info@eneka.lt			Construction site	Drawing type	
				Customer drawing	
				Drawing no.	
				NS6-V-13-01BS	
			Date	Lang.	Sheet
			11/2/2016	en	1